

Reka Cartridge Preheater KVG.LCD



Subject to modifications

Fig. Cartridge Preheater KVG.LCD

Cartridge Preheater KVG.LCD with Digital Temperature Display for 2 Hot-Melt Cartridges

The all new KVG.LCD makes a continuous workflow even more easy. Process hot-melt cartridges continuously by preheating them to the required temperature. Save time and avoid unnecessary interruptions caused by not yet usable hot-melt.

Set the temperature hassle-free down to the degree thanks to the devices' electronic temperature control with push buttons. This way you sustain the quality of the glue and keep your gluing-results at their best.

Technical Data

<i>Article Number</i>	5143 (230 V) / 5142 (120 V)
<i>Capacity</i>	2 Cartridges
<i>Cartridges</i>	Ø 47 mm – 310 ml – Length 215 mm
<i>Power Supply</i>	230 V / 50 Hz / 120 V / 60 Hz
<i>Power Consumption</i>	500 W
<i>Heat-up time</i>	approx. 10 minutes
<i>Temperature control</i>	Electronic
<i>Temperature limitation</i>	Temperature monitor
<i>Consistency of temperature</i>	± 2 °C
<i>Temperature indication</i>	digital
<i>Operating temperature</i>	50 - 160 °C
<i>Weight</i>	2740 g

Reka Klebetechnik GmbH & Co. KG
Siemensstr. 6
DE-76344 Eggenstein
Telefon: +49 721 970 780
Telefax: +49 721 705 069
E-Mail: in-fo@reka-klebetechnik.de
Internet: www.reka-klebetechnik.de