

Reka Cartridge Preheater KVG.LCD



Subject to modifications

Fig. Cartridge Preheater KVG.LCD

Cartridge Preheater KVG.LCD with Digital Temperature Display for 2 Hot-Melt Cartridges

The all new KVG.LCD makes a continuous workflow even more easy. Process hot-melt cartridges continuously by preheating them to the required temperature. Save time and avoid unnecessary interruptions caused by not yet usable hot-melt.

Set the temperature hassle-free down to the degree thanks to the devices' electronic temperature control with push buttons. This way you sustain the quality of the glue and keep your gluing-results at their best.

Technical Data

| | |
|-----------------------------------|----------------------------------|
| <i>Article Number</i> | 5143 (230 V) / 5142 (120 V) |
| <i>Capacity</i> | 2 Cartridges |
| <i>Cartridges</i> | Ø 47 mm – 310 ml – Length 215 mm |
| <i>Power Supply</i> | 230 V / 50 Hz / 120 V / 60 Hz |
| <i>Power Consumption</i> | 500 W |
| <i>Heat-up time</i> | approx. 10 minutes |
| <i>Temperature control</i> | Electronic |
| <i>Temperature limitation</i> | Temperature monitor |
| <i>Consistency of temperature</i> | ± 2 °C |
| <i>Temperature indication</i> | digital |
| <i>Operating temperature</i> | 50 - 160 °C |
| <i>Weight</i> | 2740 g |

Reka Klebetechnik GmbH & Co. KG
Siemensstr. 6
DE-76344 Eggenstein
Telefon: +49 721 970 780
Telefax: +49 721 705 069
E-Mail: in-fo@reka-klebetechnik.de
Internet: www.reka-klebetechnik.de