

## Hot-Melt Applicator MS 80



Fig. MS 80

Made in Germany

Subject to modifications

**The MS 80 glue gun works with granular hot-melts without compressed air.**

The MS 80 and MS 200 glue guns are the only glue guns working with hot-melt granulate without compressed air. Simply connect them to the socket – ready. Use the thermostatic controls to set the requested temperature between 50 °C and 200 °C and you always work with the optimum glue temperature.

Pull the trigger to apply the melted granulate. There is a great number of accessories making the MS 80 suitable for many applications. The MS 80 gets light like a feather when it is fixed to a balancer. The MS 80 has proven successful in practice over a long period of time.

## Technical Data

	MS 80	
Article Number	5551 (230 V)	5560 (120 V)
Weight	850 g	
Power Supply	230 V / 50 Hz	120 V / 60 Hz
Power Consumption	200 Watt	
Current Consumption	0,9 A	1,7 A
Degree of protection	IP 30	
Class of protection	I	
Temperature control	Thermostat	
Operating temperature	50 – 200 °C	
Consistency of temperature	± 5 °C	
Heat-up time	approx. 10 min.	
Gross Tank Capacity	150 ml	
Conveying system	Mechanics	
Length of electric cord	1,8 m	
Recommended melts	Hot-melt granulate, pillows and chips	

## Accessories

- 1 # 5563 Premelter
- 2 # 3519 Cleaning Liquid Meltanova
- 3 # 3544 Balancer
- 4 Inquire about our nozzle range

**Reka Klebetechnik GmbH & Co. KG**  
Siemensstr. 6  
DE-76344 Eggenstein  
Telefon: +49 721 970 780  
Telefax: +49 721 705 069  
E-Mail: [in-fo@reka-klebetechnik.de](mailto:in-fo@reka-klebetechnik.de)  
Internet: [www.reka-klebetechnik.de](http://www.reka-klebetechnik.de)