

Hot-Melt Applicator MS 200.2



Subject to modifications

Fig. MS 200

Made in Germany

Hot-Melt Glue Applicator Gun MS 200 – Easy Processing of Hot-Melt without compressed air.

The MS 200 lets you process hot-melt in form of 43mm sticks, granulate and pillows. The MS 200 does not require compressed air and is thanks to its 500 Watts power consumption ready to go in 5 minutes. The big filling hole makes filling the capacity of 250 ml (8.4 US fluid ounces) comfortable and reduces spillage. An unique ergonomic shape and an adjustable trigger enable the user to work comfortable and without fatigue.

The MS 200 is suited even for delicate hands and both right and lefthanders. The integrated magnetic foot proves to be a true time saver when putting down and picking up the applicator on magnetic surfaces. A wirestand provides a secure stand on nonmagnetic surfaces. In combination with a variety of available nozzles the MS 200 serves almost every application conveniently, flexibly and professionally.

Technical Data

	<i>MS 200.2</i>	
<i>Article Number</i>	<i>5579 (230 V)</i>	<i>5580 (120 V)</i>
<i>Weight</i>	<i>1220 g</i>	
<i>Power Supply</i>	<i>230 V / 50 Hz</i>	<i>120 V / 60 Hz</i>
<i>Power Consumption</i>	<i>500 Watt</i>	
<i>Current Consumption</i>	<i>2,2 A</i>	<i>4,2 A</i>
<i>Degree of protection</i>	<i>IP 30</i>	
<i>Class of protection</i>	<i>I</i>	
<i>Temperature control</i>	<i>Thermostat</i>	
<i>Temperature limitation</i>	<i>Temperature monitor</i>	
<i>Operating temperature</i>	<i>50 – 200 °C</i>	
<i>Consistency of temperature</i>	<i>± 5 °C</i>	
<i>Heat-up time</i>	<i>approx. 5 min.</i>	
<i>Gross Tank Capacity</i>	<i>250 ml</i>	
<i>Conveying system</i>	<i>Mechanics</i>	
<i>Length of electric cord</i>	<i>1,8 m</i>	
<i>Recommended melts</i>	<i>Hot-melt granulate, pillows and 43mm sticks/slugs</i>	

Accessories

- 1 # 5563 Premelter
- 2 # 3519 Cleaning Liquid Meltanova
- 3 # 3544 Balancer
- 4 # 2100 Stand for Storing
- 5 # 3465 Nozzle Set M14 Professional
- 6 Inquire about our nozzle range

Reka Klebetechnik GmbH & Co. KG
Siemensstr. 6
DE-76344 Eggenstein
Telefon: +49 721 970 780
Telefax: +49 721 705 069
E-Mail: in-fo@reka-klebetechnik.de
Internet: www.reka-klebetechnik.de